



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
09/529,773	06/30/2000	Anil K. Agarwal	A7046	3512
<div>7590 Sughrue Mion Zinn Macpeak & Seas 2100 Pennsylvania Avenue NW Washington, DC 20037-3213</div>			<div>EXAMINER DEAN, RAYMOND S</div>	
			<div>ART UNIT 2618</div>	<div>PAPER NUMBER</div>
			<div>MAIL DATE 11/02/2007</div>	<div>DELIVERY MODE PAPER</div>

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Office Action Summary	Application No. 09/529,773	Applicant(s) AGARWAL ET AL.	
	Examiner Raymond S. Dean	Art Unit 2618	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 21 August 2007.
- 2a) ☒ This action is **FINAL**. 2b) ☐ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 1-20 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 1-20 is/are rejected.
- 7) ☐ Claim(s) _____ is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☒ The drawing(s) filed on 30 June 2000 is/are: a) ☒ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some * c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
2. ☐ Certified copies of the priority documents have been received in Application No. _____.
3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).
- * See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- | | |
|--|---|
| 1) <input checked="" type="checkbox"/> Notice of References Cited (PTO-892) | 4) <input type="checkbox"/> Interview Summary (PTO-413)
Paper No(s)/Mail Date. _____ |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948) | 5) <input type="checkbox"/> Notice of Informal Patent Application |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO/SB/08)
Paper No(s)/Mail Date _____ | 6) <input type="checkbox"/> Other: _____ |

DETAILED ACTION

Response to Arguments

1. Applicant's arguments filed August 21, 2007 have been fully considered but they are not persuasive.

Examiner respectfully disagrees with Applicants' assertion on Page 10, 2nd Paragraph "There is no disclosure that of generating bit error rate messages indicating a bit error rate for a signal transmitted at N power levels." Strodbeck teaches that there is a direct relationship between the BER and the power level (See Col. 6 lines 38 – 47) thus when the power level changes there will be a corresponding change in the BER. Since the BERs change there are a plurality of BERs and thus a corresponding plurality of power levels.

Claim Rejections - 35 USC § 103

2. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

3. Claims 1 – 2, 5, 8 – 9, 19 are rejected under 35 U.S.C. 103(a) as being unpatentable over Strodbeck et al. (5,864,547) in view of Washburn et al. (4,999,583).

Regarding Claim 1, Strodbeck teaches a distributed network under the control of a computer (Figure 1, Col. 3 lines 44 – 48, typical satellite systems comprise network control centers (NCCs), which comprise at least one computer), the network having a first terminal including the amplifier, the first terminal being operatively coupled to a plurality of second terminals by a communication channel (Figure 1, Col. 3 lines 44 – 48, 4 lines 45 – 47, the VSATs can communicate with one another), said method comprising: generating bit error rate (BER) messages indicative of measured BER for a signal transmitted at N power levels (Cols. 5 lines 10 – 60, 6 lines 17 – 47, the uplink power can be a plurality of power levels, byte errors comprise bit errors), each of said BER messages including a tag indicative of a power level among the N power levels corresponding to the measured BER in each of said BER messages, at the second terminals (Cols. 5 lines 10 – 60, 6 lines 17 – 47, the error rates are an indication of the power level, for example- an improved bit error rate is an indication that the power is higher); reducing the maximum allowed power of the amplifier responsive to the BER messages (Cols. 5 lines 10 – 60, 6 lines 17 – 47).

Strodbeck does not teach reducing the maximum allowed power of the amplifier when it is determined that the amplifier is approaching saturation responsive to the generated BER messages and a method for dynamically determining the power compression point of an amplifier.

Washburn teaches reducing the maximum allowed power of the amplifier when it is determined that the amplifier is approaching saturation and a method for dynamically determining the power compression point of an amplifier (Col. 2 lines 53 – 68).

It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the amplifier of Strodbeck with the amplifier control circuitry of Washburn for the purpose of enabling the amplifier remain below its maximum safe operating level as taught by Washburn.

Regarding Claim 5, Strodbeck teaches a distributed network under the control of a computer (Figure 1, Col. 3 lines 44 – 48, typical satellite systems comprise network control centers (NCCs), which comprise at least one computer), the network having a first terminal including the amplifier, the terminal being operatively coupled to a plurality of second terminals by a communication channel (Figure 1, Col. 3 lines 44 – 48, 4 lines 45 – 47, the VSATs can communicate with one another), said method comprising: transmitting a signal transmitted at N power levels to the second terminals, where N is a positive integer (Cols. 5 lines 10 – 60, 6 lines 17 – 47, the uplink power can be a plurality of power levels); measuring a bit error rate (BER) for the signal at each of said N power levels at the second terminals (Cols. 5 lines 10 – 60, 6 lines 17 – 47); generating BER messages for the signal at each of said N power levels, each of said BER messages including the measured BER and a tag indicative of a power level among said N power levels corresponding to the measured BER in each of said BER messages (Cols. 5 lines 10 – 60, 6 lines 17 – 47, the error rates are an indication of the power level, for example- an improved bit error rate is an indication that the power is higher); transmitting the BER messages to the computer (Cols. 5 lines 10 – 60, the data, which comprises the error measurements, is re-formatted and transmitted); and

Art Unit: 2618

reducing the maximum allowed power of the amplifier responsive to the BER messages (Cols. 5 lines 10 – 60, 6 lines 17 – 47).

Strodtbeck does not teach reducing the maximum allowed power of the amplifier when it is determined that the amplifier is approaching saturation responsive to the BER messages and a method for dynamically determining the power compression point of an amplifier.

Washburn teaches reducing the maximum allowed power of the amplifier when it is determined that the amplifier is approaching saturation and a method for dynamically determining the power compression point of an amplifier (Col. 2 lines 53 – 68).

It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the amplifier of Strodtbeck with the amplifier control circuitry of Washburn for the purpose of enabling the amplifier remain below its maximum safe operating level as taught by Washburn.

Regarding Claims 2, 8, Strodtbeck in view of Washburn teaches all of the claimed limitations recited in Claims 1, 5. Strodtbeck further teaches wherein N is an integer greater than 2 (Cols. 5 lines 10 – 60, 6 lines 17 – 47, the uplink power can be a plurality of power levels, which comprises a numbers greater than 2), and wherein said reducing the maximum allowed power comprises: determining an average BER responsive to said generated BER messages (Col. 6 lines 30 – 47, the number of errors is averaged); determining a BER slope responsive to said determined average BER (Figure 4, Col. 6 lines 30 – 47); and reducing the maximum allowed power when the

Art Unit: 2618

BER slope is indicative of lower slope at higher power levels (Figure 4, Col. 6 lines 30 – 47, region 104 of plot represents the lower slope).

Regarding Claim 9, Strodbeck in view of Washburn teaches all of the claimed limitations recited in Claim 5. Strodbeck further teaches determining an average BER responsive to said generated BER messages (Col. 5 lines 10 – 60, the number of errors is averaged); determining a BER slope responsive to said determined average BER (Figure 4, Col. 6 lines 30 – 47); and evaluating the BER slope with respect to a reference power-BER data stored in the computer (Figure 4, Cols. 5 lines 57 – 60, 6 lines 30 – 47, the look-up table provides the storage, .00125, .0225 is the reference BER); and reducing the maximum allowed power when the determined BER slope and said reference power-BER data diverge to thereby indicate a lower slope at higher power levels (Figure 4, Col. 6 lines 30 – 47, region 104 of plot represents the divergence).

Regarding Claim 19, Strodbeck in view of Washburn teaches all of the claimed limitations recited in Claim 5. Strodbeck further teaches wherein the transmitting the signal at the N power levels further comprises: transmitting a first plurality of signals at a high power level H; transmitting a second plurality of signals at a medium power level M; and transmitting a third plurality of signals at a low power level L (Col. 6 lines 38 – 47, Strodbeck teaches that there is a direct relationship between the BER and the power level thus when the power level changes there will be a corresponding change in the BER, Since the BERs change there are a plurality of BERs and thus a corresponding plurality of power levels).

Art Unit: 2618

4. Claims 3 – 4, 6 – 7 are rejected under 35 U.S.C. 103(a) as being unpatentable over Strodbeck et al. (5,864,547) in view of Washburn et al. (4,999,583), as applied to Claim 1 above, and further in view of Ichiyoshi (5,991,280).

Regarding Claim 3, Strodbeck in view of Washburn teaches all of the claimed limitations recited in Claim 1. Strodbeck in view of Washburn does not teach wherein the signal is a control burst.

Ichiyoshi teaches wherein the signal is a control burst (Abstract).

It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the system of Strodbeck in view of Washburn with the control burst of Ichiyoshi for the purpose of synchronizing the VSATs without depending on a GPS system as taught by Ichiyoshi.

Regarding Claims 4, 7, Strodbeck in view of Washburn and further in view of Ichiyoshi teaches all of the claimed limitations recited in Claims 3, 6. Washburn further teaches the control burst in N sequential frames, wherein N is an integer greater than or equal to 2 (Abstract, in a TDMA system typical control bursts are greater than 2 frames).

Regarding Claim 6, Strodbeck in view of Washburn teaches all of the claimed limitations recited in Claim 5. Strodbeck further teaches wherein the communication channel comprises a satellite (Figure 1, Col. 3 lines 44 – 48).

Strodbeck in view of Washburn does not teach wherein the signal is a control burst.

Ichiyoshi teaches wherein the signal is a control burst (Abstract).

It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the system of Strodbeck in view of Washburn with the control burst of Ichiyoshi for the purpose of synchronizing the VSATs without depending on a GPS system as taught by Ichiyoshi.

5. Claims 10 – 18 are rejected under 35 U.S.C. 103(a) as being unpatentable over Strodbeck et al. (5,864,547) in view of Ichiyoshi (5,991,280).

Regarding Claim 10, Strodbeck teaches a method for dynamic uplink power control for an amplifier in a distributed network under the control of a computer (Figure 1, Col. 3 lines 44 – 48, 4 lines 45 – 47, typical satellite systems comprise network control centers (NCCs), which comprise at least one computer), the network having a first terminal being operatively coupled to a plurality of second terminals by a communication channel (Figure 1, Col. 3 lines 44 – 48, 4 lines 45 – 47, the VSATs can communicate with one another), said method comprising: examining a plurality of bit error rate measurement reports, respectively corresponding to a signal transmitted at N power levels. (Col. 5 lines 10 – 60, 6 lines 17 – 47, the uplink power can be a plurality of power levels); computing an average BER responsive to said examined plurality of the BER measurement reports (Col. 5 lines 10 – 60, the number of errors is averaged); when said computed average BER is greater than said predetermined BER threshold, increasing a power level of the amplifier (Figure 4, Col. 6 lines 30 – 47, region 106); and when said computed average BER is less than a predetermined BER threshold, decreasing the power level of amplifier (Figure 4, Col. 6 lines 30 – 47, region 104).

Art Unit: 2618

Strodtbeck does not teach a control burst.

Ichiyoshi teaches wherein the signal is a control burst (Abstract).

It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the system of Strodtbeck with the control burst of Ichiyoshi for the purpose of synchronizing the VSATs without depending on a GPS system as taught by Ichiyoshi.

Regarding Claim 14, Strodtbeck teaches a method for dynamic uplink power control for an amplifier in a distributed network under the control of a computer (Figure 1, Col. 3 lines 44 – 48, 4 lines 45 – 47, typical satellite systems comprise network control centers (NCCs), which comprise at least one computer), the network having a first terminal including the amplifier, the first terminal being operatively coupled to a plurality of second terminals by a communication channel (Figure 1, Col. 3 lines 44 – 48, 4 lines 45 – 47, the VSATs can communicate with one another), said method comprising: examining a plurality of bit error rate measurement reports respectively corresponding to a signal transmitted at N power levels (Col. 5 lines 10 – 60); computing an average BER responsive to said examined plurality of the BER measurement reports (Col. 5 lines 10 – 60, the number of errors is averaged); comparing said computed average BER with a predetermined BER threshold (Figure 4, Col. 6 lines 30 – 47, region 106); when said computed average BER is greater than said predetermined BER threshold, increasing a power level of the amplifier (Figure 4, Col. 6 lines 30 – 47, region 106); and when said average BER is less than said predetermined

Art Unit: 2618

BER threshold, decreasing the power level of amplifier (Figure 4, Col. 6 lines 30 – 47, region 104).

Strodtbeck does not teach a control burst.

Ichiyoshi teaches wherein the signal is a control burst (Abstract).

It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the system of Strodtbeck with the control burst of Ichiyoshi for the purpose of synchronizing the VSATs without depending on a GPS system as taught by Ichiyoshi.

Regarding Claims 11, 15, Strodtbeck in view of Ichiyoshi teaches all of the claimed limitations recited in Claims 10, 14. Strodtbeck further teaches determining whether the power level of the amplifier is greater than a predetermined maximum power level; and when it is determined that the power level is greater than said predetermined maximum power level, varying at least one characteristic of a signal carried by the communications channel so as to reduce the BER (Col. 6 lines 30 – 47, an improved BER corresponds to a change in the transmit power).

Regarding Claims 12, 16, Strodtbeck in view of Ichiyoshi teaches all of the claimed limitations recited in Claims 10, 14. Strodtbeck further teaches determining whether the power level of the amplifier is greater than a predetermined maximum power level; and when the power level is greater than said predetermined maximum power level, establishing binary phase shift keying (BPSK) as a signal modulation technique to modulate the signal transmitted at the N power levels (Col. 5 lines 3 – 8, when the power level is greater than or less than the predetermined maximum power

Art Unit: 2618

level BPSK used or QPSK is used); and when the power level is less than said predetermined maximum power level, establishing quadrature phase shift keying (QPSK) as the signal modulation technique to modulate the signal transmitted at the N power levels (Col. 5 lines 3 – 8, when the power level is greater than or less than the predetermined maximum power level BPSK used or QPSK is used).

Regarding Claims 13, 17, Strodtbeck in view of Ichiyoshi teaches all of the claimed limitations recited in Claim 12, 16. Strodtbeck further teaches wherein said determining step is performed following said increasing the power level of the amplifier (Col. 4 lines 45 – 49, the UPLC is adaptive to mitigate the effect of interference and rain fade thus there will be a constant determining after the increasing thus enabling the power to be constantly adjusted).

Regarding Claim 18, Strodtbeck in view of Ichiyoshi teaches all of the claimed limitations recited in Claim 14. Strodtbeck further teaches determining up and down power values U and D, respectively, based on the computed average BER and a target BER; and wherein said increasing the power level comprises increasing power level of the amplifier by U dB (Figure 4, Cols. 4 lines 45 – 49, 6 lines 30 – 47); said decreasing the power level comprises decreasing the power level of the amplifier by D dB (Figure 4, Cols. 4 lines 45 – 49, 6 lines 30 – 47); and U and D are real numbers stored in a database of the computer (Figure 4, Col. 5 lines 57 – 60, look-up table is the database).

Art Unit: 2618

6. Claim 20 is rejected under 35 U.S.C. 103(a) as being unpatentable over Strodbeck et al. (5,864,547) in view of Washburn et al. (4,999,583), as applied to Claim 19 above, and further in view of Fleming et al. (US 6,212,360)

7. Regarding Claim 20, Strodbeck in view of Washburn teaches all of the claimed limitations recited in Claim 19. Strodbeck in view of Washburn does not teach wherein $H = P_1 - h$ (dB), $M = P_1 - m$ (dB), and $L = P_1 - l$ (dB), wherein P_1 is a 1 dB compression of the amplifier, $h = 1$ dB, $m = 2$ dB; and $l = 3$ dB, and wherein the maximum allowed power of the amplifier is H .

Fleming teaches wherein $H = P_1 - h$ (dB), $M = P_1 - m$ (dB), and $L = P_1 - l$ (dB), wherein P_1 is a 1 dB compression of the amplifier, $h = 1$ dB, $m = 2$ dB; and $l = 3$ dB, and wherein the maximum allowed power of the amplifier is H (Cols. 8 lines 61 – 67, 9 lines 1 – 7, 9 lines 13 – 24, the power is adjusted to a plurality of levels thus the power level can be adjusted in the above increments).

It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the system of Strodbeck in view of Washburn with the power control method of Fleming for the purpose of achieving good E_b/N_0 margins as taught by Fleming.

Conclusion

8. **THIS ACTION IS MADE FINAL.** Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

Art Unit: 2618

A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the mailing date of this final action.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Raymond S. Dean whose telephone number is 571-272-7877. The examiner can normally be reached on Monday-Friday 6:00-2:30.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Edward F. Urban can be reached on 571-272-7899. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Art Unit: 2618

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.



Raymond S. Dean
October 22, 2007



EDWARD F. URBAN
SUPERVISORY PATENT EXAMINER
TECHNOLOGY CENTER 2600